

## LDPE Lupolen 2426 H

### Product Description

Lupolen 2426 H is an additivated , low density Polyethylene. It contains slip and anti-blocking agent. It is delivered in pellet form.

### Applications

- Cast Film
- Bags&Pouches
- Film &Shrink
- Film Blown Film
- Surfacen Protection Film

### Processing Method

- Cast Film
- Blown Film

### Features

Unspecified Antiblocking, Opticals, Good Process ability, Unspecified Slip, Low Friction

### Producer

Amir Kabir Petrochemical Company

No	Property	Value	Units	Test Method
1	Density	0.924	g/cm <sup>3</sup>	ISO 1183
2	Melt flow rate (MFR)(190°C/2.16Kg)	1.9	g/10 min	ISO 1133
3	Tensile Modulus	260	MPa	ISO 527-1, -2
4	Tensile Stress at Yield	11	MPa	ISO 527-1, -2
5	Tensile Strength MD/TD	26/18	MPa	ISO 527-1, -3
6	Tensile Strain at Break MD/TD	250/600	%	ISO 527-1, -3
7	Dart Drop Impact(50 blown film)	110	g	ASTM D 1709
8	Vicat softening temp(A50 (50 °C/h 10N))	94	°C	ISO 306
9	Haze (50)	<9.0	%	ASTM D 1003
10	Gloss (60 °,50)	>100		ASTM D 2457

